

1125



The Tally Dascom 1125, is a 24 pin, 80 column serial dot matrix printer with USB, parallel and serial interfaces as standard. Compact in size, the 1125 is perfect for industrial environments and front and back office applications where space is limited.

With low running costs, high quality output and an easy to use control panel it's ideal for small business, low volume listings and reports, as well as dispatch notes and labels.

Highlights at a glance:

- Compact 24-pin narrow carriage printer
- Up to 500 characters per second
- Ideal for front and back office applications
- Auto switching USB, parallel and serial interface
- Long life ribbon
- Small footprint

In addition to these applications, the 1125 is also well suited to measurement and control systems. Amongst the lowest priced matrix printers available today the 1125 also offers a long life ribbon giving this printer very low running costs.

For draft printing it's considerably less expensive running costs make it a viable alternative to low cost inkjet printers.

Available Configuration:

- **1125** Standard Product

1125

Print Speed	375 cps (Fastest Draft); 250 cps (Draft), 83 cps (LQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	295 pages per hour
Character density	10, 12, 15, 17.1, 20 cpi
Line density	1, 2, 3, 4, 6, 8 lpi
Printhead life	400 million strokes per pin
Memory	68 kB
Standard Connectivity	USB 2.0, Parallel (Bi-directional) and Serial RS232
Standard Emulations	IBM ProPrinter 2390 Plus, Epson LQ /ESC P/2)
Fonts	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 10 Barcodes
Consumables	Black ribbon: 7 million characters
Standard Paper Handling	Push tractor and single sheet tray
Number of Copies	1 Original + 4 copies
Paper Type	Continuous forms, cut sheet
Paper Weight	52-100 g/m ²
Paper Size	Width: 3" to 10"
Physical Weight	11 lbs
Physical Size	14.1" x 11.2" x 6.2" (W x D x H)
Noise Level (ISO 7779)	51 dB(A)
Power Voltage	120 V and 220 V models available
Power Consumption	3,8 W Stand-By
Temperature	+5° to +40° C; 10% to 80% humidity (not condensing)
Print Volume	6.000 pages per month
MTBF	10.000 hours
Warranty	1 year return to depot
Printer Drivers	Windows 98/2000/XP/Vista/7 and Server 2003/2008

DASCOM Americas Corporation

421 West Main Street
Waynesboro, Virginia
USA 22980-3606
Tel: 877 434 1377
www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 