

## LA2610



*Tally*  
**DASCOM**

The Tally Dascom LA2610 is a highly featured, reliable and stylish machine. Performance and workload, ergonomics, maintainability, excellent price – everything has been incorporated to ensure it is the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors.

### Highlights at a glance:

- Print speeds **up to 680 cps**
- **20,000 pages per month** workload
- 136 columns
- 24 pin print head produces excellent print quality
- **Straight through paper path** for easy forms loading
- Ethernet, parallel and USB interfaces standard
- **LC Display** for easy operation
- Includes DEC PPL2 command set and MMJ Adapter

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

DEC compatible printers continue to be in demand. These printers are particularly suited to DEC Servers, DEC VAX and Alpha, in VMS and OpenVMS operating environments.

### Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service new bar code standard will require this capability to take advantage of the best rates available.



#### Configurations:

- **LA2610** Standard Product

## LA2610

<b>Print Speed</b>	680 cps (Fastest Draft); 500 cps (HS-Draft), 333 cps (Draft), 111 cps (LQ) at 10 cpi
<b>Resolution</b>	up to 360 x 360 dpi
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	500 million dots per wire
<b>Memory</b>	128 kB
<b>Standard Connectivity</b>	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT), Serial RS232, DEC MMJ Adapter included
<b>Optional Connectivity</b>	N/A
<b>Standard Emulation</b>	DEC PPL2, IBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCP
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing
<b>Consumable</b>	Ribbon: 8 million characters
<b>Standard Paper Handling</b>	One tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off
<b>Optional Paper Handling</b>	Additional push tractor (rear)
<b>Number of Copies</b>	Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 1 copy; Cut sheet: 1 original + 5 copies
<b>Paper Type</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper Weight</b>	60-120 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 76 to 420 mm, 3.0 to 16.5 in; Length: 76 to 599 mm, 3.0 to 23.6 in
<b>Physical Weight</b>	10,6 kg, 23.3 lbs
<b>Physical Size</b>	600 x 265 x 200 mm, 23.6 x 10.4 x 7.9 in (W x D x H)
<b>Acoustic</b>	52 dB(A)
<b>Power Voltage</b>	100 - 240 V wide range auto-sensing
<b>Power Consumption</b>	40 Watt Printing; <10 W Sleep Mode
<b>Temperature</b>	+10° to +40° C; 10% to 85% humidity
<b>Workload</b>	20.000 pages per month
<b>MTBF</b>	20,000 hours
<b>Drivers</b>	Windows 2000/XP/Vista/7/8 and Server 2003/2008; SAP

### DASCOM Americas

113 Mill Place Parkway

Verona, VA 24482

Phone 877-434-1377 – Fax: 540-242-7221

[www.dascomamericas.com](http://www.dascomamericas.com)

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 