

## T2265+



*Tally*

The T2265+ and T2280+ are undoubtedly at the pinnacle of serial impact printing, representing the peak of performance in their respective speed segments. They are not just sprinters; reliable, heavy workload output is guaranteed for the many years following their purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

### Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service new bar code standard will require this capability to take advantage of the best rates available.

Sample Intelligent Mail Barcode



### Highlights at a glance:

- Print speeds up to 900 cps
- Full range of automatic features minimising operator intervention
- Ideal for 'On-Demand' and 'Batch' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard.
- Optional Serial RS232, IBM AS400/iSeries Mainframe Ethernet IPDS

Fully automatic operation instills operator confidence and virtually eliminates errors caused by poor user intervention. Front feed provides all the benefits of easy forms installation, coupled with reliable paper transport.

The products are well matched to Microsoft Windows applications, and entirely suited to other host operating environments, including legacy systems. The T2265+ and T2280+ printers are the first high speed matrix printers to incorporate Ethernet on-board.




Available Configuration:

- **T2265+** Standard Product

## T2265+

<b>Print Speed</b>	900 cps (Fastest Draft); 640 cps (Draft), 180 cps (NLQ) at 10 cpi
<b>Resolution</b>	up to 360 x 360 dpi
<b>Throughput</b> (ECMA 132)	610 pages per hour
<b>Character Density</b>	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	500 million strokes per pin
<b>Memory</b>	128 kB
<b>Standard Connectivity</b>	Parallel (Bi-directional) and Ethernet 10/100 BaseT
<b>Optional Connectivity</b>	RS-232 Serial, Ethernet with SCS or IPDS, Coax/Twinax with SCS or IPDS
<b>Standard Emulations</b>	IBM ProPrinter XL24, Epson LQ (ESC P/2), MTPL + Barcode + LCP, Genicom ANSI
<b>Optional Emulations</b>	ECAM 9014, MT460D, MT50, IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and scaleable LCP
<b>Consumables</b>	Ribbon: 20 million characters
<b>Standard Paper Handling</b>	Push tractor for continuous paper with straight paper path, tear off and park position
<b>Optional Paper Handling</b>	Additional push tractor (front), Automatic cutting device
<b>Number of Copies</b>	Push tractor front: 1 original + 5 copies
<b>Paper Type</b>	Continuous forms, multi-part forms
<b>Paper Weight</b>	60-120 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 3" to 16.5"; Length: 3" to 22"
<b>Physical Weight</b>	45 lbs
<b>Physical Size</b>	24.5" x 17" x 11" mm (W x D x H)
<b>Acoustic</b>	55 dB(A)
<b>Power Voltage</b>	120 V or 230 V (selectable)
<b>Power Consumption</b>	65 Watt Printing
<b>Temperature</b>	+10° to +35° C; 20% to 80% humidity (not condensing)
<b>Workload</b>	48.000 pages per month
<b>MTBF</b>	10.000 hours
<b>Drivers</b>	Windows 2000/XP/Vista/7 and Server 2003/2008; SAP
<b>Warranty</b>	90 days on-site warranty
<b>Note</b>	For OCR applications it is recommended that your readers are tested. Paper is a highly variable medium and should be tested prior to purchase.

**DASCOM Americas Corporation**  
 421 West Main Street  
 Waynesboro, Virginia  
 USA 22980-3606  
 Tel: 877 434 1377  
 www.dascom.com

SERIAL MATRIX PRINTERS   
 MOBILE PRINTERS   
 FLATBED PRINTERS   
 THERMAL PRINTERS 