

T2380



Tally

“Unsurpassed excellence”. That defines the rugged high powered T2380 printer. Built to leave a lasting impression on your productivity, this high speed workhorse exemplifies what rugged durability is all about. With its advanced 24-pin print head, the 2380 is engineered to perform at a blistering pace even in the harshest of operating environments. You’re assured of top-shelf performance, crisp, clear and reliable print quality and a machine you can count on when your performance is what counts.

Low running costs and durability in the harshest of print environments make these products excellent value for money.

Highlights at a glance:

- Full range of automatic features to minimize user intervention
- Ideal for ‘On-Demand’ and ‘Batch’ applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard.
- Optional Interfaces: RS232 Serial; Coax/Twinax; Ethernet IPDS
- Compatible with a wide range of operating systems including Windows, UNIX, DOS, SAP R3 and legacy systems

These products are well matched to Microsoft Windows applications, and highly compatible with other host operation environments including legacy systems.

Fully automated operation, coupled with the ‘straight through’ paper path, allows ease of use and virtually eliminates errors caused by user intervention.

Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service new bar code standard will require this capability to take advantage of the best rates available.

Sample Intelligent Mail Barcode






Available Configuration:

- **T2380** Standard Product
- **T2380 2T** with additional rear tractor

T2380

| | |
|--------------------------------|---|
| Print Speed | 1.000 cps (Fastest Draft); 800 cps (Draft), 222 cps (NLQ) at 10 cpi |
| Resolution | up to 360 x 360 dpi |
| Throughput (ECMA 132) | 680 pages per hour |
| Character Density | 5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi |
| Line Density | 2, 3, 4, 6, 8, 12 lpi |
| Printhead Life | 750 million strokes per pin |
| Standard Memory | 128 kB |
| Standard Connectivity | Parallel (Bi-directional) and Ethernet 10/1q00 BaseT |
| Optional Connectivity | RS-232 Serial, Ethernet with SCS or IPDS, Coax/Twinax with SCS or IPDS |
| Standard Emulation | IBM ProPrinter XL24, Epson LQ (ESC P/2), MTPL + Barcode + LCP, Genicom ANSI |
| Optional Emulation | PCL 3 (Rugged Writer), IGP/PGL, Code V, MT660, Printronix P6000, HP2564C |
| Fonts | HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and scaleable LCP |
| Consumables | Ribbon: 20 million characters |
| Standard Paper Handling | Push tractor for continuous paper with straight paper path, tear off and park position |
| Optional Paper Handling | Additional push tractor (front), Automatic cutting device |
| Number of Copies | Push tractor front: 1 original + 5 copies Push tractor rear: 1 original + 3 copies (2T version) |
| Paper Type | Continuous forms, multi-part forms |
| Paper Weight | 60-120 g/m ² |
| Paper Size | Width: 3" to 16.5"; Length: 3" to 22" |
| Physical Weight | 19 kg |
| Physical Size | 24.5" x 17" x 11" mm (W x D x H) |
| Acoustic | 59 dB(A) |
| Power Voltage | 120 V or 230 V (selectable) |
| Power Consumption | 70 Watt Printing; 18 W Power-Save |
| Temperature | +10° to +35° C; 20% to 80% humidity (not condensing) |
| Workload | 50.000 pages per month |
| MTBF | 12.500 hours |
| Warranty | 90 days on-site warranty |
| Drivers | Windows 2000/XP/Vista/7 and Server 2003/2008; SAP |
| Note | For OCR applications it is recommended that your readers are tested. Paper is a highly variable medium and should be tested prior to purchase. |

DASCOM Americas Corporation
 421 West Main Street
 Waynesboro, Virginia
 USA 22980-3606
 Tel: 877 434 1377
 www.dascom.com

SERIAL MATRIX PRINTERS 
 MOBILE PRINTERS 
 FLATBED PRINTERS 
 THERMAL PRINTERS 