

T2440/24



Tally

DASCOM's mid range T2440 serial matrix printers are designed for applications where fast throughput and flexible paper management are vital.

Forms are easy to load as the paper is loaded either at the front or the rear of the printer. For precise paper control and to enable feeding of continuous forms, the push tractor can also be used as a pull tractor.

The printer features a long life 24 pin print head providing compatibility with Oki and Epson 24 pin emulations. All printers support graphics and barcodes systems.

Highlights at a glance:

- Print speeds up to 576 cps
- 80 columns
- Tractor feed and Manual insertion; ideal for invoices, reports, general office documents
- Reliable and durable
- USB and Parallel standard interfaces
- Optional integrated Ethernet (10/100BaseT) and Serial RS232 available
- Quick change, long life ribbon in this class

With auto switching USB, parallel interfaces as standard and an optional Ethernet or serial interface, these new dot matrix printers offer a cost effective solution.

With high print speeds of up to 576 characters per second and the ability to handle different types of print media, including labels, invoices, reports and multi part forms, they are well suited for back office applications, including retail, local government, healthcare, warehousing and distribution.

Available Configuration:





- **T2440/9** 9 pin version/80 column

T2440

Print Speed	576 cps (Fastest Draft); 480 cps (Draft), 133 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360
Throughput (ECMA 132)	395 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	1, 2, 3, 4, 6, 8, 12 lpi
Printhead Life	400 million characters
Memory	256 kB
Standard Connectivity	Parallel (Bi-directional) and USB 2.0
Standard Emulation	IBM ProPrinter XL24, Epson ESC P/2, Oki Superset Commands
Fonts	HS Draft, Draft, Courier, Quadrato, OCR-A/B
Consumables	Ribbon: 8 million characters
Standard Paper Handling	Push tractor (rear) or pull tractor (front) and cut sheet insertion
Number of Copies	1 original + 4 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 3" to 10' mm
Physical Weight	14.3 lbs
Physical Size	15.7" x 13" x 5.3" (W x D x H)
Acoustic	52 dB(A)
Power Voltage	120 V - 50/60 Hz
Power Consumption	51 Watt Printing; <7 W Sleep Mode
Temperature	+10° to +40° C; 20% to 85% humidity
Workload	20.000 pages per month
MTBF	15.000 hours
Drivers	Windows 2000/XP/Vista/7 and Server 2003/2008
Warranty	1 year return to depot

DASCOM Americas Corporation

421 West Main Street
Waynesboro, Virginia
UAS 22980-3606
Tel: 877 434 1377
www.dascom.com

SERIAL MATRIX PRINTERS 
MOBILE PRINTERS 
THERMAL PRINTERS 
LINE MATRIX PRINTERS 
LASER PRINTERS 