

# LA48N/LA48W

**Quiet, fast, high quality printing  
optimized for the DEC® environment**



*Tally*

The narrow-carriage LA48N and wide-carriage LA48W are designed for a broad spectrum of applications and are specially optimized for the DEC® environment. There's support for DEC®ANSI, IBM® ProPrinter® X24e, and Epson® ESC/P2 emulation.

The 24-pin print head produces clear, crisp output of texts and graphics. The printer has nineteen resident fonts and eight resident bar code fonts ensuring fast, high quality text and dependable bar code printing.

- **Print speeds up to 400cps @ 10cpi (LA48N); 448cps @ 10cpi (LA48W)**
- **24-pin print head for clear, crisp output of text and graphics**
- **Standard parallel with USB or Serial interface**
- **Print head protection**
- **Auto interface switching on multiple I/F version**
- **Quiet operation**

The printer offers simple switching of paper types and auto tear-off functionality. Parking continuous forms makes it easy to switch between continuous forms and single sheets. Continuous forms are automatically fed up to the tear-off position at the end of each job.

With a maximum noise level of only 49 dB(A) the LA48N and LA48W are very quiet printers compared with many competitive models.

Available Configuration:

- LA48N 80 column, Parallel/USB
- LA48N 80 column, Parallel/Serial RS 232
- LA48W 136 column, Parallel/USB
- LA48W 136 column, Parallel/Serial RS 232

SERIAL MATRIX  
PRINTERS

MOBILE  
PRINTERS

THERMAL  
PRINTERS

LINE MATRIX  
PRINTERS

LASER  
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE





# LA48N/LA48W

<b>Print Speed</b>	10 cpi: High Speed Draft 400 (LA48N), 448 (LA48W); Draft 360; LQ 113
<b>Print Method</b>	Serial Impact
<b>Resolution</b>	Up to 360 x 360 dpi (ESC/P Emulation only)
<b>Throughput</b>	319 pages per hour (ECMA 132)
<b>Character Density</b>	10, 12, 15, 17.1, 18, 20 cpi
<b>Line Density</b>	1, 2, 3, 4, 6, 7, 8 lpi
<b>Printhead Life</b>	400 M strokes per needle
<b>Standard Connectivity</b>	(model variants) Parallel/USB; Parallel/Serial RS232; All 128K input
<b>Optional Connectivity</b>	External Ethernet 10/100baseT
<b>Standard Emulation</b>	DEC ANSI PPL2, IBM® Proprinter, Epson® LQ (ESC P/2)
<b>Fonts</b>	Bitmap fonts: Courier 10, Prestige Elite 12, Boldface PS, Compressed Draft 12 High-speed draft 12, OCR-B 10, OCR-A 10, Correspondence 10, PCIA 10, Scalable Fonts: Courier, Nimbus Sans®, Timeless (Normal, Bold, Italic), 8 barcodes
<b>Consumables</b>	4 M Character Ribbon
<b>Standard Paper Handling</b>	Auto tear; manual continuous/cut sheet switch; manual paper thickness adjustment.
<b>Number of Copies</b>	Original + 4 (5-part forms)
<b>Form Thickness</b>	Max. 0.35mm (.014 in.)
<b>Paper Type</b>	Continuous forms and Cut forms
<b>Paper Size</b>	LA48N: Cut sheet: width 4.01-10.51 inches, length 2.99-14.33 inches, continuous forms: width 4.01-10.51 inches, length over 4 inches; LA48W: Cut sheet: width 4.01-16.53 inches, length 2.99-16.53 inches Continuous forms: width 4.01-16.53 inches, length over 4 inches
<b>Physical Weight</b>	LA48N: 7.3 Kg (16 lbs.); LA48W: 9.7 Kg (16 lbs.)
<b>Physical Size (HxWxD)</b>	LA48N: 4.72 X 16.33 X 12.99 inches, LA48W: 4.72 X 22.44 X 12.99 inches
<b>Power Voltage</b>	120V
<b>Power Consumption Printing</b>	90W, Sleep Mode: max 10W (LA48N), max 28W (LA48W)
<b>Workload</b>	Up to 8,000 pages per month
<b>Reliability MTBF</b>	20,000 hours @ 25% duty cycle
<b>Drivers</b>	Windows 9x/ME, 2000, 2003 Server, XP, Vista
<b>Temperature</b>	+5°C to +38°C
<b>Humidity</b>	30% to 80%
<b>Acoustic</b>	49dB(A)
<b>Warranty</b>	1 year return to depot

**Note: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.**

**DASCOM Americas Corporation**  
421 West Main Street  
Waynesboro, Virginia  
USA 22980-3606  
Tel: 877 434 1377  
[www.dascom.com](http://www.dascom.com)

Copyright © 2010 DASCOM Americas Corporation  
All rights reserved. All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

SERIAL MATRIX PRINTERS   
MOBILE PRINTERS   
THERMAL PRINTERS   
LINE MATRIX PRINTERS   
LASER PRINTERS 