



The smart choice in value-driven point-of-sale receipt printers

The RT322 Series from OKI®: cost-efficient performance right out of the box—backed by up to 2 years of Overnight Exchange coverage.¹

User-, customer- and budget-friendly – RT322 Series printers are the ideal choice for point-of-sale applications. Their compact size, fast print speed and high-quality output make them perfect for your establishment.

These direct thermal printers are designed for simplicity. Their compact footprint can be positioned for either horizontal or vertical use. To load, the top flips open and a roll of media drops in. Interchangeable interfaces let them grow right along with your business. And there's virtually no operating learning curve.

With a capability of printing over 33 receipts a minute,² the RT322 Series can keep productivity levels high—and your customers satisfied.

Superior technology gets the job done – The high print quality of RT322 Series printers ensures easy readability. 203 dpi resolution is especially appropriate for reproducing barcodes, including 2D barcodes—when embedding more

data is required, as in coupon printing, delivery order tickets, and return receipts. These printers also give you the ability to print in two colors.³

RT322 Series printers are at home in most Windows® environments. Models come with parallel, serial, high-speed USB or network connectivity standard. User-installable optional interfaces let you upgrade when needed.

The RT322SK Liner-Free model is designed to work with repositionable thermal labels that stick to virtually any surface, and are easily removed and reapplied, leaving behind no residue. This is ideal for use in libraries, quick-service food restaurants, warehouse applications, retail, and medical and diagnostic environments.

Unmatched customer support – All RT322 Series printers come with an Overnight Exchange limited warranty.¹ And, if you need technical assistance, you can speak to a live OKI expert located in North America by calling, toll free, 800-OKI-DATA (800-654-3282) at any time.⁴

The RT322 Series from OKI: the smart choice in POS receipt printers.

Highlights

- Direct Thermal receipt printer
- High-quality 203 dpi print quality
- Barcode printing capability, including 2D
- Interchangeable connectivity interfaces
- “Drop-In & Print” paper loading
- Up to 6 ips (150 mm/sec.) print speed—equals up to 33 receipts per minute²
- Liner-free (SK) model available
- Overnight Exchange limited warranty¹
- Live, toll-free technical support 24/7/365⁴



¹ RT322 models – 2-Year limited warranty; RT322SK model – 1-Year limited warranty. Available in the U.S. and Canada only.

² With USB 2.0 interface. 20 lines plus graphic. Published performance results based on laboratory testing. Individual results may vary.

³ Requires special media.

⁴ Available in the U.S. and Canada only.

RT322 Series

Specifications		
Technology	Print Method	Direct Thermal
	Print Speed	Up to 6 ips or 150 mm/sec.
	Max Print Width	80 mm paper = 72 mm; 58 mm paper = 52 mm
	Resolution	203 dpi (8 dots per mm)
	Flash ROM	16 MB
	Logo Storage	2 MB Flash ROM (requires graphic management software, included)
Interfaces	Standard	Models available with Parallel, 25-pin Serial, USB v2.0 or Ethernet connectivity
Compatibility	Operating Systems	Drivers available: Windows® Vista® (32-/64-bit) , 2000 /Server (32-bit), XP (32-bit)
	Emulations	ESC/POS™, Star Line/T
Fonts & Graphics	Character Set	ANK 95, 32 Int 128 Graphic
	No. of Columns	48 or 64
	Line Spacing	3 mm, 4 mm, Programmable
	2-Color Printing	Red & Black, Blue & Black (requires special media)
	Linear Barcodes	UPC-A, JAN/EAN-8, JAN/EAN-13, Code 39, ITF, Code 128, Code 93, NW-7
	2-Dimensional Barcodes	PDF417
Paper Handling	Media Type	Roll paper; Liner-free, repositionable thermal label rolls (RT322SK only)
	Media Width	80 mm standard; 58 mm (paper guide)
	Media Roll Diameter	3.27" (83 mm)
	Autocutter	Partial cut (center cut)
	Paper Loading	"Drop-In & Print"
	Paper Sensors	Paper End; Near End (for horizontal and vertical use)
Environmental	Size (WxDxH)	5.59" x 7.95" x 5.19" (142 mm x 202 mm x 132 mm)
	Weight	Autocutter 3.79 lb. (1.72 Kg); Tear bar 3.44 lb. (1.56 Kg)
	Power Consumption	Operating 1.8 Amp average; Standby 0.15 Amp
	Operating Temperature	41° F – 113° F (5° C – 45° C); 10%–90% RH, non-condensing
	Storage Temperature	-4° F – 140° F (-20° C – 60° C); 10%–90% RH, non-condensing
Reliability	Printhead	60 million lines (MCBF)
	Autocutter	1 million cuts
Warranty	Standard	RT322 Models – 2-Year limited warranty with Overnight Exchange ² RT322SK Model – 1-Year limited warranty with Overnight Exchange ²

Ordering Information	
Description	Part Numbers
RT322cp (Cutter – Parallel) Charcoal	62115203
RT322cs (Cutter – Serial) Charcoal	62115403
RT322cu (Cutter – USB) Charcoal	62115603
RT322cn (Cutter – Network) Charcoal	62115803
RT322tp (Tear – Parallel) Charcoal	62115205
RT322ts (Tear – Serial) Charcoal	62115405
RT322tu (Tear – USB) Charcoal	62115605
RT322tn (Tear – Network) Charcoal	62115805
RT322cu SK (Cutter – USB) Charcoal	92307101
Options	
Vertical Stand Kit	70056301
Warning Buzzer (Ticket Alarm)	70056001

¹ Published performance results based on laboratory testing. Individual results may vary.

² Available in the U.S. and Canada only.

Specifications are subject to change without notice.

© 2013 Oki Data Americas, Inc. OKI Reg. T.M., M.R., OKI Electric Industry Co., Ltd. Windows, Vista Reg. T.M., Microsoft Corp. ESC/POS T.M., Seiko Epson Corp. USB I/F logo T.M., Universal Serial Bus Implementers Forum, Inc.

For more information on POS Printers from OKI, contact your OKI representative. Or visit our Web site: www.okidata.com



OKI DATA AMERICAS, INC.

USA
2000 BISHOPS GATE BLVD.
MOUNT LAUREL, NJ 08054-4620
TEL: 800.OKI.DATA (800.654.3282)
FAX: 856.222.5320

CANADA
4140B SLADEVIEW CRESCENT
UNITS 7 & 8
MISSISSAUGA, ONTARIO L5L 6A1
TEL: 905.608.5000
FAX: 905.608.5040

LATIN AMERICA
2000 BISHOPS GATE BLVD.
MOUNT LAUREL, NJ 08054-4620
TEL: 856.231.0002
FAX: 856.222.5071

OKI DATA DE MÉXICO, S.A. DE C.V.
MARIANO ESCOBEDO, 748 8º PISO
COL. NUEVA ANZURES C.P. 11590
MÉXICO, D.F.
TEL: 55.5263.8780
FAX: 55.5250.3501

OKI DATA DO BRASIL INFORMÁTICA LTDA.
AV. ALFREDO EGÍDIO DE SOUZA ARANHA, 100
BLOCO C – 4º ANDAR
04726-170 – SÃO PAULO – SP – BRASIL
TEL: 11.3444.3500
FAX: 11.3444.3502

WWW.OKIDATA.COM

Printed in the USA

MS15957-0613