

T2340/24

The Ultimate In Document Printing



Tally

DASCOM's mid range serial matrix printers include the T2240/T2340 series products. Very popular transaction printers, they feature great ergonomics. Forms are easy to load as the paper's installed at the front, not the rear. With automatic top of form and zero tear the printers are easy to set up with no wasted forms.

The products are ideal for back office applications which include retail, local government, hospitals, warehousing and ditribution. They include printing labels, shipping documents and multipart forms.

- **High quality 24 pin printhead**
- **Narrow (80 columns - T2240) and wide format versions (136 columns - T2340) available**
- **Front feed for easy paper loading and reliable paper transport**
- **Zero tear, paper park, automatic top of form for ease of use**
- **Wide range of emulations for easy connection to a wide range of hosts**
- **Manual feed: front in, front out; ideal for cheques, statements, registration cards**

Narrow and wide format machines offer the choices of small footprint and diverse range of forms.

In line with market demands, the new printers are quieter and easier to use than competitive products in their class. All products support graphics and barcodes.

Available Configuration:

T2340/24 24 pin version

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

T2340/24

| | |
|--------------------------------|--|
| Print Speed | At 10 cpi; Draft: 409 cps, Copy Draft 275 cps, NLO: 92 cps |
| Throughput | T2x40/24: Letter Performance 368; Spreadsheet 175. |
| Character Density | 10, 12, 15, 17.1, 20 cpi |
| Line Density | 3, 4, 6, 8, 12 lpi |
| Printhead Life | 300 million characters (draft) |
| Memory | 64Kb |
| Standard Connectivity | Parallel (Bi-directional) |
| Optional Connectivity | Serial RS232, external ethernet 10/100baseT, USB - parallel adapter |
| Standard Emulation | MTPL, IBM ProPrinter XL24e, Epson LQ850+/LQ1050+/Esc PEpson® ESC/P2 |
| Fonts | Draft, Draft Copy, Courier, Roman, Sans Serif, Prestige Elite, Script, OCR-A/B*, 13 barcodes, scaleable LCP fonts, OCR-A and 10 barcodes |
| Consumables | Ribbon: 4 million characters |
| Standard Paper Handling | Tractor paper - push tractors with paper parking, view and tear at top of form cut sheet front insertion with integrated table |
| Optional Paper Handling | 2nd push tractor |
| Paper Type | Continuous forms and cut forms |
| Paper Weight | Continuous Forms 60-120gsm. Cut sheet 80-120gsm |
| Paper Size | Width: 3–16.5"; Length: Continuous Forms: 3"-22"; Cut Forms:3"-14" |
| Physical Weight | Approximately 24.25lbs |
| Physical Size | (HxWxD): 24.6" x 9.7" x 7.9" |
| Power Voltage | AC 120V +/- 10% OR AC 220V - 240V +/- 10% |
| Power Consumption | 55W printing |
| Workload | 14,000 pages per month |
| Number of Copies | 1+3 Standard, 1+4 Heavy Mode |
| Acoustic | 53dB(A) |
| Warranty | 1 year return to depot |
| Option 1 | Push tractors, front; automatic cut sheet feeder, front |

Note: Exceeding the monthly duty cycle will not void the warranty if DASCAM consumables and maintenance kits are used.